

85

DESCRIPTION:

Omega 85 "Shear Sensation Plus" (SSP) all-purpose grease is an improved version of unique and continuing Omega research into the development of a single grease to meet virtually any automotive and industrial application. "Shear Sensation Plus" (SSP) is an improved formulation and features the same phenomenal shear stability that remains unmatched by any ordinary grease!

UNMATCHED SHEAR STRENGTH:

Through extensive laboratory and field testing, Omega engineers have further improved the shear stability built into Omega 85 "Shear Sensation Plus", while retaining Omega 85's truly multi-purpose functionality.

INBUILT COMPATIBILITY:

Omega 85 SSP continues to be fully compatible with bearing seal materials such as hytrel, viton and neoprene. It also provides excellent compatibility with soap-thickened greases (such as lithium-based) and will not adversely co-react when used in such applications where residuals of these may remain.

TRUE MULTI-PURPOSE CAPABILITY:

With Omega 85 SSP, there is virtually no limit to application recommendations. It can be applied with superlative lubrication results in automotive and industrial plain and anti-friction bearings, in hot or cold environments and subjected to light, medium or heavy loads even over super-extended periods of operation.

SUPERIOR TEMPERATURE STABILITY:

Omega 85 "Shear Sensation Plus" (SSP) features an improved dropping point in excess of 520°F (270°C) for the NLGI # 2 grade coupled with the legendary continuously-effective Extreme Pressure performance and thermally-stable base oil. Omega 85 SSP continues to be eminently suited for prolonged superlative lubrication performance at elevated temperatures.

Due to the especially improved high quality base oil used and good penetration properties built into Omega 85, it retains its excellent low temperature lubrication characteristics.

SUPERIOR THICKENER AND ADDITIVES PACKAGE:

Omega 85 SSP's unique, advanced and improved constituents provide outstanding resistance to water and encompasses a "moisture-lock" to provide excellent protection against rust. It therefore effectively tolerates wet working environments. In continuing development testing, Omega 85 SSP retains its superlative properties after 3,000 hours in the ASTM-D-3336 long-life bearing test at 300°F (1,000 hours is already considered outstanding performance) !!!

Omega 85 "Shear Sensation Plus" continues to stand out as a superior multi- purpose grease that covers virtually the entire spectrum of lubrication applications in the automotive and industrial field and fully the equal of the widest range of applications, environment and application conditions to be found anywhere.

Omega 85 SSP also continues to provide extended superior performance and represents the highest-level of technical excellence in the field of lubrication ever developed for commercial applications.



TYPICAL DATA:

TEST	ASTM TEST METHOD	TEST RESULT	
		NLGI#2	NLGI#0
Mineral Oil Base: -			•
Viscosity, cSt at 40°C (104°F)	D-445	126	126
Viscosity, cSt at 100°C (212°F)	D-445	11.7	11.7
Viscosity Index	D-2270	75	75
Unworked Penetration @ 77°F	D-217	278	362
Worked Penetration: -			
60 Strokes	D-217	280	366
10,000 Strokes	D-217	293	376
100,000 Strokes	D-217	310	-
Dropping Point, °C (°F)	D-2265	270 (520)	257 (495)
Roll Stability (% Change)	D-1831	292 (+4.3)	410 (+10.2)
Rust Prevention	D-1743	Pass	
Timken, OK Load, Lbs	D-2509	60	-
Oil Separation, % Loss	D-1742	0.3	-
Four-Ball Wear Protection, Scar Diameter, mm	D-2266	0.4	0.37
Four-Ball EP Performance			
Load Wear Index	D-2596	100	-
Weld Point, Kgf	D-2596	500	400
Water Washout			
Percentage (%) Loss, @ 100°F		N/A	N/A
Percentage (%) Loss, @ 175°F		2	
Mobility at 0°F, gm/sec	USS Method	0.20	0.64
Operating Temperature Range °C (°F)	-	-25 to 200°C (-13 to 392°F)	
Color	-	Royal Blue	

Omega 85 "Shear Sensation Plus" exceeds the requirements of specification NLGI GC/LB (ASTM D-4950).





Product name: Omega 85 - "Shear Sensation Plus" All-Purpose Page: 1/11

Grease NLGI #2

Supersedes date: 2019-02-18 Last revised date: 2023-01-18

Product No.: SDS-ID: GB-EN/4.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: Omega 85 - "Shear Sensation Plus" All-Purpose Grease NLGI #2

Container size: 400 g, 5 kg, 15 kg, 55 kg, 200 kg

1.2. Relevant identified uses of the substance or mixture and uses advised against

<u>Application:</u> Lubricating grease.

<u>Identified use(s):</u> For professional users only.

1.3. Details of the supplier of the safety data sheet

Supplier: GB importer:

ITW PP & F Korea Limited

13th Fl., Unit B, PAX Tower 609 Eonju-ro, Gangnam-Gu

Seoul, Korea 06108 Tel:+82-2-2088-3560 Fax:+82-2-513-3567

magna@magnagroup.com www.magnagroup.com

Further information can be

obtained from: magna@magnagroup.com

1.4. Emergency telephone number

Emergency telephone:

Manufacturer:

Call a Poison Center, emergency number or doctor/physician.

NHS: 111

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP: The product is not classified.

2.2. Label elements

The substance/mixture does not meet the criteria for classification, but the

Sovereign Lubricants (UK) Ltd, Crowtrees Lane,

Rastrick, West Yorkshire, HD6 3LZ

T: 01484 718674 - F: 01484 400164

enquiries@sovereign-omega.co.uk

www.sovereign-omega.co.uk

following labelling must be applied:

Safety data sheet available on request.

2.3. Other hazards

<u>PBT/vPvB:</u> This product does not contain any PBT or vPvB substances.

Other: Prolonged or repeated contact with skin may cause redness, itching, irritation,

eczema, skin cracking and oil acne. The harmful effects may increase in used

grease.

Product name: Omega 85 - "Shear Sensation Plus" All-Purpose 2/11 Page:

Grease NLGI #2

Supersedes date: 2019-02-18 2023-01-18 Last revised date:

Product No.: SDS-ID: GB-EN/4.0

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Only classified substances above threshold limits are shown.

All substances in the product are either registered or exempt from registration under REACH.

CLP:

<u>%:</u> REACH Reg. No: Chemical name: Hazard classification: CAS-No.: EC No.: Notes:

5-15 43136-14-7 01-0000015620-79- 3,3'-Dioctadecyl-1,1'-Aquatic Chronic 4;H413

XXXX methylenebis(4,1phenylene)diurea

10254-57-6 233-593-1 01-2119969655-20 4,4'-Methylene bis

3-5 (dibutyldithiocarbamate)

DMSO < 3% (IP 346) Notes:

References: The full text for all hazard statements is displayed in section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Inhalation: Move into fresh air and keep at rest. In case of persistent throat irritation or

coughing: Seek medical attention and bring these instructions.

Remove contaminated clothing immediately and wash skin with soap and water. Skin contact:

In case of rashes, wounds or other skin disorders: Seek medical attention and

bring along these instructions.

Immediately flush with plenty of water for at least 15 minutes. Remove any Eye contact:

contact lenses and open eyelids widely. If irritation persists: Seek medical

attention and bring along these instructions.

Immediately rinse mouth and drink 1-2 glasses of water or milk. Keep person Ingestion:

under observation. Do not induce vomiting. If vomiting occurs, keep head low.

Immediate transport to hospital. Bring along these instructions.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically.

Omega 85 - "Shear Sensation Plus" All-Purpose Product name: 3/11 Page:

Grease NLGI #2

Supersedes date: 2019-02-18 Last revised date: 2023-01-18

Product No.: SDS-ID: GB-EN/4.0

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Small fires: Extinguish with carbon dioxide or dry powder.

Larger fires: Extinguish with foam, carbon dioxide or dry powder. Do not use water jet as an extinguisher, as this will spread the fire.

Move container from fire area if it can be done without risk.

5.2. Special hazards arising from the substance or mixture

Specific hazards: During fire, gases hazardous to health may be formed.

Do not allow runoff to sewer, waterway or ground.

5.3. Advice for firefighters

fighters:

Protective equipment for fire- Selection of respiratory protection for fire fighting: follow the general fire

precautions indicated in the workplace.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes. Eliminate all sources of ignition. Follow Personal precautions:

precautions for safe handling described in this safety data sheet.

6.2. Environmental precautions

Environmental Do not discharge into drains, water courses or onto the ground.

precautions:

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Absorb in vermiculite, dry sand or earth and place into containers. Clean

contaminated area with oil-removing material.

6.4. Reference to other sections

References: For personal protection, see section 8.

For waste disposal, see section 13.

Product name: Omega 85 - "Shear Sensation Plus" All-Purpose Page: 4/11

Grease NLGI #2

Supersedes date: 2019-02-18 Last revised date: 2023-01-18

Product No.: SDS-ID: GB-EN/4.0

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

<u>Safe handling advice:</u> Observe good chemical hygiene practices. Avoid prolonged and repeated contact

with grease, particularly used grease. Always remove grease with soap and

water or skin cleaning agent, never use organic solvents.

<u>Technical measures:</u> Work practice should minimise contact.

Do not eat, drink or smoke when using the product.

<u>Technical precautions:</u> When working with heated grease, mechanical ventilation may be required.

7.2. Conditions for safe storage, including any incompatibilities

<u>Technical measures for safe</u> No special precautions.

storage:

Storage conditions: Store in tightly closed original container. Store at moderate temperatures in dry,

well ventilated area. (5-40°C) Protect against direct sunlight.

7.3. Specific end use(s)

Specific use(s): No information available.

Product name: Omega 85 - "Shear Sensation Plus" All-Purpose Page: 5/11

Grease NLGI #2

Supersedes date: 2019-02-18 Last revised date: 2023-01-18

Product No.: SDS-ID: GB-EN/4.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No occupational exposure limit assigned.

8.2. Exposure controls

<u>Engineering measures:</u> Provide adequate ventilation. When working with heated grease, mechanical

ventilation may be required. Provide access to washing facilities incl. soap,

skin cleanser and fatty cream.

<u>Personal protection:</u> Personal protection equipment should be chosen according to the CEN

standards and in discussion with the supplier of the personal protective

equipment.

Respiratory equipment: In case of inadequate ventilation use suitable respirator. Use respiratory

equipment with particle filter, type P2.

<u>Hand protection:</u> Risk of contact: Wear protective gloves. Nitrile gloves are recommended.

Breakthrough time: > 4h, Thickness: > 0.3 mm

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

<u>Eye protection:</u> Risk of contact: Wear goggles/face shield.

Skin protection: Wear appropriate clothing to prevent repeated or prolonged skin contact.

<u>Hygiene measures:</u> Wash hands after contact. Change contaminated clothing.

Environmental Exposure

Controls:

Not available.

Product name: Omega 85 - "Shear Sensation Plus" All-Purpose Page: 6/11

Grease NLGI #2

Supersedes date: 2019-02-18 Last revised date: 2023-01-18

Product No.: SDS-ID: GB-EN/4.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<u>Physical state:</u> Liquid. / Grease.

Colour: Blue.

Odour: Characteristic.

Odour threshold: Not available.

pH: Not available.

Melting point / freezing point: Not available.

Boiling point: Not available.

Evaporation rate:

Flammability (solid, gas):

Explosive limits

Vapour pressure:

Vapour density:

Not available.

Not available.

Not available.

Solubility: Immiscible with water

Partition coefficient (n-

octanol/water):

Relative density:

Flash point:

Not available.

1,038 (20°C)

>200 °C

<u>Auto-ignition</u> Not available.

temperature (°C):

<u>Decomposition</u> Not available.

temperature (°C):

<u>Viscosity:</u> Not available. <u>Explosive properties:</u> Not available. <u>Oxidising properties:</u> Not available.

9.2. Other information

Other data: No information available.

Product name: Omega 85 - "Shear Sensation Plus" All-Purpose Page: 7/11

Grease NLGI #2

Supersedes date: 2019-02-18 Last revised date: 2023-01-18

Product No.: SDS-ID: GB-EN/4.0

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity: Not reactive.

10.2. Chemical stability

<u>Stability:</u> Stable under normal temperature conditions.

10.3. Possibility of hazardous reactions

<u>Hazardous Reactions:</u> None known.

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight. Protect from moisture.

10.5. Incompatible materials

<u>Incompatible materials:</u> Avoid contact with acids and oxidising substances.

10.6. Hazardous decomposition products

<u>Hazardous decomposition</u> During fire, gases hazardous to health may be formed.

products:

Product name: Omega 85 - "Shear Sensation Plus" All-Purpose Page: 8/11

Grease NLGI #2

Supersedes date: 2019-02-18 Last revised date: 2023-01-18

Product No.: SDS-ID: GB-EN/4.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

The harmful effects may increase in used grease.

Acute Toxicity (Oral): Based on available data, the classification criteria are not met.

Acute Toxicity (Dermal): Based on available data, the classification criteria are not met.

Acute Toxicity (Inhalation): Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Respiratory or skin

Based on available data, the classification criteria are not met.

sensitisation:

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

<u>Carcinogenicity:</u> Based on available data, the classification criteria are not met.

Reproductive Toxicity: Based on available data, the classification criteria are not met.

STOT - Single exposure: Based on available data, the classification criteria are not met.

STOT - Repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Inhalation: Inhalation of oil mist or vapours formed during heating of the product will irritate

the respiratory system and provoke coughing.

Skin contact: Degreasing. Prolonged or repeated contact with skin may cause redness, itching,

irritation and eczema/chapping.

Eye contact: Direct contact may irritate.

<u>Ingestion:</u> May irritate and cause malaise.

Specific effects: Prolonged or repeated contact with used grease may cause serious skin

diseases, such as dermatitis.

11.2. Information on other hazards

Endocrine disrupting

The product does not contain any substance identified as having endocrine

<u>properties:</u> disrupting properties.

Product name: Omega 85 - "Shear Sensation Plus" All-Purpose Page: 9/11

Grease NLGI #2

Supersedes date: 2019-02-18 Last revised date: 2023-01-18

Product No.: SDS-ID: GB-EN/4.0

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

<u>Ecotoxicity:</u> Greases are generally hazardous to the environment.

12.2. Persistence and degradability

<u>Degradability:</u> The product is expected to be slowly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT/vPvB: This product does not contain any PBT or vPvB substances.

12.6. Endocrine disrupting properties

Endocrine disrupting The product does not contain any substance identified as having endocrine

properties: disrupting properties.

12.7. Other adverse effects

Other adverse effects: None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste.

Waste from residues: EWC-code: 20 01 26

<u>Contaminated packaging:</u> Dispose of contaminated packings as residue.

Product name: Omega 85 - "Shear Sensation Plus" All-Purpose Page: 10/11

Grease NLGI #2

Supersedes date: 2019-02-18 Last revised date: 2023-01-18

Product No.: SDS-ID: GB-EN/4.0

SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/AND/RID).

14.1. UN number

<u>UN-No:</u>

14.2. UN proper shipping name

Proper Shipping Name:

14.3. Transport hazard class(es)

Class: -

14.4. Packing group

PG: -

14.5. Environmental hazards

Marine pollutant: -

Environmentally Hazardous

substance:

14.6. Special precautions for user

Special precautions: Not relevant.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk: Not relevant.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulation: UK Statutory Instruments, 2021 No. 904, CONSUMER PROTECTION

ENVIRONMENTAL PROTECTION HEALTH AND SAFETY. The REACH etc.

(Amendment) Regulations 2021.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006 with amendments.

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No.

2677) with amendments.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019 (SI 2019 No.

720), as amended.

EH40/2005, Workplace exposure limits 2005, with amendments.

The List of Wastes (England) (Amendment) Regulations 2005. (SI 2005 No. 895).

15.2. Chemical Safety Assessment

<u>CSA status:</u> No chemical safety assessment has been carried out.

Product name: Omega 85 - "Shear Sensation Plus" All-Purpose Page: 11/11

Grease NLGI #2

Supersedes date: 2019-02-18 Last revised date: 2023-01-18

Product No.: SDS-ID: GB-EN/4.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

The following sections contain revisions or new statements: 1, 2, 3, 4, 5, 6, 7, 11, 12, 13, 15, 16.

Omega Manufacturing Division 13th floor, Unit B, PAX Tower, 609 Eonju-ro, Gangnam-Gu, Seoul, Korea 06108

Tel: +82-2-2088-3560 Fax: +82-2-513-3567

Web site: www.magnagroup.com

The Omega Trade Mark is the property of ITW, Inc., and is used under license by ITW PP & F Korea Limited.

Abbreviations and acronyms

<u>used in the safety data sheet:</u> CSA= Chemical Safety Assessment.

PBT = Persistent, Bioaccumulative and Toxic. vPvB = very Persistent and very Bioaccumulative.

Additional information: Classification according to Regulation (EC) No. 1272/2008: Calculation method.

Wording of H-statements:

H413 May cause long lasting harmful effects to aquatic life.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

 $\label{eq:made_problem} \mbox{Made by DHI - Environment and Toxicology, Agern All\'e 5, DK-2970 H\"{o}rsholm, Denmark.} \\ \mbox{www.dhigroup.com}.$