

【定格総荷重表】



■9.6m~36.2mブーム

| 作業半径 (m) | 9.6m ブーム | 16.25m ブーム | 22.9m ブーム | 29.55m ブーム | 36.2m ブーム |
|----------|-------------|---------------|--------------|---------------|--------------|
| 3.0 | 35.00 | 22.50 | 15.50 | 10.00 | |
| 3.5 | 30.60 | 22.50 | 15.50 | 10.00 | 7.00 |
| 4.0 | 27.50 | 22.50 | 15.50 | 10.00 | 7.00 |
| 4.5 | 24.70 | 20.70 | 15.50 | 10.00 | 7.00 |
| 5.0 | 22.50 | 19.30 | 15.50 | 10.00 | 7.00 |
| 5.5 | 20.60 | 17.90 | 14.40 | 10.00 | 7.00 |
| 6.0 | 19.10 | 16.80 | 13.45 | 10.00 | 7.00 |
| 6.5 | 16.70 | 15.80 | 12.55 | 10.00 | 7.00 |
| 7.0 | 13.00 | 14.90 | 11.85 | 10.00 | 7.00 |
| 8.0 | | 13.10 | 10.60 | 9.00 | 7.00 |
| 9.0 | | 11.20 | 9.60 | 8.05 | 6.40 |
| 10.0 | | 9.45 | 8.60 | 7.25 | 5.80 |
| 11.0 | | 7.90 | 7.80 | 6.60 | 5.30 |
| 12.0 | | 6.50 | 7.05 | 6.05 | 4.90 |
| 13.0 | | 5.50 | 6.30 | 5.55 | 4.50 |
| 14.0 | | | 5.45 | 5.10 | 4.15 |
| 15.0 | | | 4.70 | 4.70 | 3.85 |
| 16.0 | | | 4.10 | 4.35 | 3.60 |
| 17.0 | | | 3.60 | 4.05 | 3.35 |
| 18.0 | | | 3.10 | 3.60 | 3.15 |
| 19.0 | | | 2.70 | 3.15 | 2.95 |
| 20.0 | | | 2.30 | 2.80 | 2.75 |
| 22.0 | | | | 2.15 | 2.40 |
| 24.0 | | | | 1.60 | 1.85 |
| 26.0 | | | | 1.20 | 1.45 |
| 28.0 | | | | | 1.05 |
| 30.0 | | | | | 0.75 |
| 32.0 | | | | | 0.50 |
| 33.0 | | | | | 0.40 |
| 危険角度 | — | — | — | — | — |

(単位: ton)

| 作業半径 (m) | 9.6m ブーム | 16.25m ブーム | 22.9m ブーム | 29.55m ブーム | 36.2m ブーム |
|----------|-------------|---------------|--------------|---------------|--------------|
| 3.0 | 35.00 | 22.50 | 15.50 | 10.00 | |
| 3.5 | 30.00 | 22.50 | 15.50 | 10.00 | 7.00 |
| 4.0 | 22.20 | 20.60 | 15.50 | 10.00 | 7.00 |
| 4.5 | 17.40 | 16.60 | 15.50 | 10.00 | 7.00 |
| 5.0 | 14.15 | 13.40 | 13.90 | 10.00 | 7.00 |
| 5.5 | 11.80 | 11.10 | 12.00 | 10.00 | 7.00 |
| 6.0 | 10.00 | 9.35 | 10.30 | 10.00 | 7.00 |
| 6.5 | 8.60 | 8.00 | 8.90 | 9.00 | 7.00 |
| 7.0 | 7.50 | 6.90 | 7.75 | 8.10 | 7.00 |
| 8.0 | | 5.25 | 6.00 | 6.50 | 6.65 |
| 9.0 | | 4.05 | 4.80 | 5.25 | 5.50 |
| 10.0 | | 3.15 | 3.85 | 4.30 | 4.55 |
| 11.0 | | 2.45 | 3.15 | 3.55 | 3.80 |
| 12.0 | | 1.75 | 2.55 | 2.95 | 3.20 |
| 13.0 | | 1.20 | 2.10 | 2.50 | 2.70 |
| 14.0 | | | 1.60 | 2.10 | 2.30 |
| 15.0 | | | 1.20 | 1.70 | 1.95 |
| 16.0 | | | 0.85 | 1.35 | 1.60 |
| 17.0 | | | 0.55 | 1.00 | 1.30 |
| 18.0 | | | | 0.75 | 1.00 |
| 19.0 | | | | 0.50 | 0.75 |
| 20.0 | | | | | |
| 22.0 | | | | | |
| 24.0 | | | | | |
| 26.0 | | | | | |
| 28.0 | | | | | |
| 30.0 | | | | | |
| 32.0 | | | | | |
| 33.0 | | | | | |
| 危険角度 | — | — | 25° | 42° | 53° |

(単位: ton)

| 作業半径 (m) | 9.6m ブーム | 16.25m ブーム | 22.9m ブーム | 29.55m ブーム | 36.2m ブーム |
|----------|-------------|---------------|--------------|---------------|--------------|
| 3.0 | 35.00 | 22.50 | 15.50 | 10.00 | |
| 3.5 | 30.60 | 22.50 | 15.50 | 10.00 | 7.00 |
| 4.0 | 27.50 | 22.50 | 15.50 | 10.00 | 7.00 |
| 4.5 | 24.70 | 20.70 | 15.50 | 10.00 | 7.00 |
| 5.0 | 22.50 | 19.30 | 15.50 | 10.00 | 7.00 |
| 5.5 | 20.60 | 17.90 | 14.40 | 10.00 | 7.00 |
| 6.0 | 17.50 | 16.65 | 13.45 | 10.00 | 7.00 |
| 6.5 | 14.90 | 14.05 | 12.55 | 10.00 | 7.00 |
| 7.0 | 12.85 | 12.10 | 11.85 | 10.00 | 7.00 |
| 8.0 | | 9.25 | 10.00 | 9.00 | 7.00 |
| 9.0 | | 7.25 | 8.10 | 8.05 | 6.40 |
| 10.0 | | 5.85 | 6.65 | 6.95 | 5.80 |
| 11.0 | | 4.75 | 5.50 | 6.00 | 5.30 |
| 12.0 | | 3.90 | 4.65 | 5.10 | 4.90 |
| 13.0 | | 3.20 | 3.90 | 4.35 | 4.50 |
| 14.0 | | | 3.35 | 3.75 | 3.90 |
| 15.0 | | | 2.85 | 3.25 | 3.45 |
| 16.0 | | | 2.40 | 2.80 | 3.05 |
| 17.0 | | | 1.95 | 2.45 | 2.65 |
| 18.0 | | | 1.60 | 2.10 | 2.35 |
| 19.0 | | | 1.25 | 1.75 | 2.00 |
| 20.0 | | | 1.00 | 1.45 | 1.70 |
| 22.0 | | | | 0.95 | 1.20 |
| 24.0 | | | | 0.55 | 0.80 |
| 26.0 | | | | | 0.50 |
| 28.0 | | | | | |
| 30.0 | | | | | |
| 32.0 | | | | | |
| 33.0 | | | | | |
| 危険角度 | — | — | — | 20° | 35° |

(単位: ton)

| 作業半径 (m) | 9.6m ブーム | 16.25m ブーム | 22.9m ブーム | 29.55m ブーム | 36.2m ブーム |
|----------|-------------|---------------|--------------|---------------|--------------|
| 3.0 | 16.40 | 14.80 | 13.90 | 10.00 | |
| 3.5 | 12.35 | 11.60 | 11.40 | 10.00 | 7.00 |
| 4.0 | 9.75 | 9.05 | 9.50 | 8.90 | 7.00 |
| 4.5 | 7.90 | 7.25 | 8.00 | 7.90 | 7.00 |
| 5.0 | 6.50 | 5.90 | 6.75 | 6.90 | 6.20 |
| 5.5 | 5.45 | 4.90 | 5.70 | 6.00 | 5.55 |
| 6.0 | 4.60 | 4.05 | 4.80 | 5.30 | 5.00 |
| 6.5 | 3.95 | 3.40 | 4.15 | 4.60 | 4.50 |
| 7.0 | 3.40 | 2.85 | 3.55 | 4.00 | 4.05 |
| 8.0 | | 2.00 | 2.65 | 3.05 | 3.25 |
| 9.0 | | 1.20 | 2.00 | 2.40 | 2.60 |
| 10.0 | | 0.55 | 1.40 | 1.85 | 2.05 |
| 11.0 | | | 0.90 | 1.40 | 1.60 |
| 12.0 | | | | 1.00 | 1.20 |
| 13.0 | | | | | |
| 14.0 | | | | | |
| 15.0 | | | | | |
| 16.0 | | | | | |
| 17.0 | | | | | |
| 18.0 | | | | | |
| 19.0 | | | | | |
| 20.0 | | | | | |
| 22.0 | | | | | |
| 24.0 | | | | | |
| 26.0 | | | | | |
| 28.0 | | | | | |
| 30.0 | | | | | |
| 32.0 | | | | | |
| 33.0 | | | | | |
| 危険角度 | — | 40° | 54° | 61° | 67° |

(単位: ton)